



**Backing:** Foil/Scrim/Kraft Paper Laminate

**Adhesive:** Acrylic

**Liner:** Polycoated Natural Kraft Paper

**Colors:** Aluminum

**Specifications:** UL 723 Classified ( $\leq$  72mm)  
Meets FAR 25.853(a)

**Standard Sizes:** 72mm x 46M

### Applications

- Vapor barrier seal for insulation facing
- Sealing insulation and repairing in cooler/refrigeration applications

### Features

- Foil/Scrim/Kraft Laminate Backing
- High Performance Acrylic Adhesive
- UL 723 Classified and Meets FAR 25.853(a)
- Low VOC Content

### Benefits

- High strength and tear resistant
- UV, moisture, and mold resistant
- Low odor
- High tack, aggressive bond to surfaces
- Excellent performance in extreme cold or heat
- Meets flammability requirements for use in construction, aerospace, and marine applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	9.5 mils	0.241 mm	ASTM D-1000
<b>Adhesion to Steel</b>	75 oz/in	8.21 N/cm	PSTC 101
<b>Tensile Strength</b>	33 lb/in	57.79 N/cm	ASTM D-1000
<b>Operating Temperature</b>	-35 to 260 °F	-37 to 127 °C	
<b>Minimum Application Temp</b>	-5 °F	-20 °C	
<b>Smoke Developed</b>	0		
<b>Flame Spread</b>	0		
<b>VOC Content</b>	<30 g/L		

Recommended Storage Conditions: 32-90 °F at 50% RH  $\pm$  2%

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.