



SECTION 1 - IDENTIFICATION

Manufacturer:

Black Swan Mfg. Co.
4540 W. Thomas St.
Chicago, IL 60651-3318
Tel.: 800-252-5796
Fax: 773-227-3705
Web Site : www.blackswanmfg.com
E-mail : info@blackswanmfg.com

For any Transportation or Medical Chemical Emergencies call:

INFOTRAC(800) 535-5053 **OR** (352) 323-3500

24 hours per day - 7 days a week

Product Name: No-Hub Sealant**Recommended Use:** A sealant specifically designed as a coating for cast iron pipe to improve leak-free sealing of no-hub couplings.

SECTION 2 – HAZARD(S) IDENTIFICATION

Labels

Health Hazard Flammable

Signal Word

Danger

HMIS

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0

NEPA**HEALTH HAZARD**

4 – Deadly
3 – Extreme Danger
2 – Hazardous
1 – Slight Hazardous
0 – Normal Material

SPECIFIC HAZARD

Oxidizer OX
Acid ACID
Alkali ALK
Corrosive COR
Use NO WATER
Radioactive

**FIRE HAZARD**

Flash Points
4 – Below 73°F
3 – Below 100°F
2 – Above 100°F, Not exceeding 200°F
1 – Above 200°F
0 – Will not burn

REACTIVITY

4 – May detonate
3 – Shock and heat may detonate
2 – Violent chemical change
1 – Unstable if heated
0 – Stable

GHS Classification**Health**

Acute Toxicity: Not Established

Skin Irritation: Not Established

Eye Irritation: Not Established

Skin Sensitization: NO

Environmental

Acute Aquatic Toxicity: Not Established

Chronic Aquatic Toxicity: Not Established

Physical

Flammability: Cat. 2

Hazardous Statements

H225: Highly flammable liquid and vapor
H304: May be fatal if swallowed and enters airways
H312: Harmful in contact with skin
H319: Causes serious eye irritation
H332: Harmful if inhaled
H335: May cause respiratory irritation
H336: May cause drowsiness or dizziness

Precautionary Statements

P102: Keep out of reach of children
P103: Read label before use
P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233/P235: Keep container tightly closed and cooled
P243: Take precautionary measures against static discharge
P261: Avoid breathing dust/fume/gas/mist/vapors/spray
P262: Do not get in eyes, on skin, or on clothing
P264: Wash thoroughly after handling
P270: Do not eat, drink or smoke when using this product
P271: Use only outdoors or in a well-ventilated area
P280/P284: Wear protective gloves/protective clothing/eye protection/face protection. Wear a NIOSH approved respirator for organic solvents.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemicals	CAS#	EINECS#	REACH Pre-registration Number	Approx %
ETHYL ALCOHOL	64-17-5	200-578-6	N/A	25-30%
METHYL ALCOHOL	67-56-1	200-659-6	N/A	1-2%
ETHYL ACETATE	141-78-6	205-500-4	N/A	<1%
ACETONE	67-64-1	200-662-2	N/A	35-45%
POLYVINYL BUTYRAL	7723-18-5	N/A	N/A	10-20%

*Unlisted ingredients are not classified as hazardous according to OSHA 1910.1200.

SECTION 4 – FIRST-AID MEASURES

Inhalation: Move into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and call physician.**Skin:** Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.**Eyes:** Flush with water for 15 minutes. If irritation persists, get medical attention.**Ingestion:** Give 1 or 2 glasses of water. DO NOT INDUCE VOMITING. Contact physician immediately.

GHS SAFETY DATA SHEET

SECTION 5 – FIRE-FIGHTING MEASURES

Fire Hazard: Vapors may travel considerable distance to sources of ignition and flash back.
Combustion Products: None.
Extinguishing Media: Foam, Carbon Dioxide, Dry Chemical.
Unsuitable Extinguishing Media: None Known.
Protective Equipment: Self-contained breathing apparatus {(SCBA), MSHA/NIOSH}. Full protective gear.
Special Fire Fighting Procedures: Evacuate enclosed areas, stay upwind. Closed or confined quarters require self-contained breathing apparatus, positive pressure hose masks or airline masks. Use agents appropriate for surrounding fires.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions: None.
Protective Equipment: Wear suitable respiratory protective equipment.
Emergency Procedures: None.
Environmental Precautions: Avoid runoff into storm sewers, ditches and waterways.
Methods for Cleaning Up: Absorb with suitable inert material. Remove all sources of ignition.

SECTION 7 – HANDLING AND STORAGE

Handling

Use good personal hygiene practice. Avoid inhalation of vapors and personal contact with the product. Repeated and prolonged overexposure to solvents may cause brain and nervous system damage. Concentrating and inhaling the contents may be harmful or fatal.

Storage

Keep and store in a cool, dry place from sources of ignition. Ground during transfer. Keep container tightly closed when not in use.
Incompatible Materials: Strong oxidizing agents, strong acids.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Hazardous Chemicals</u>	<u>Exposure Limits</u>		
	<u>ACGIH-TLV</u>	<u>ACGIH-STEL</u>	<u>OSHA-PEL</u>
ETHYL ALCOHOL	1000 ppm	N/A	1000 ppm
METHYL ALCOHOL	200 ppm	N/A	200 ppm
ETHYL ACETATE	400 ppm	N/A	400 ppm
ACETONE	500 ppm	750 ppm	1000 ppm

Engineering Controls: A source of running water to flush or wash the eyes and skin in case of contact.
Ventilation: Mechanical.
Personal Protective Equipment – Respiratory: If use conditions generate vapors or mists, wear a NIOSH-approved respirator appropriate for those emission levels. Appropriate respirators may be a full face piece or a half mask air-purifying cartridge respirator equipped for organic vapors/mists, a self-contained breathing apparatus in the pressure demand mode, or a supplied-air respirator.
Personal Protective Equipment – Skin: Impermeable gloves. Chemical resistant coveralls.
Personal Protective Equipment – Eyes: Safety glasses with side shields or chemical goggles.

SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

Appearance:	Amber Viscous Liquid	Flash Point:	65°F (T.C.C.)	Vapor Pressure:	Not Established
Odor:	Characteristic Solvent	Specific Gravity:	Approx. 0.70	Flammability:	Not Established
pH:	Not Established	Solubility (H₂O):	Insoluble	Flammability Limits:	LEL – 0.9%
Melting Point:	Not Established	Evaporation Rate:	> 1.0		UEL – 7.0%
Freezing Point:	Not Established	Vapor Density:	> 1.0		
Boiling Point:	170°F	VOC:	250 g/l		

GHS SAFETY DATA SHEET

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable.

Hazardous polymerization: Will not occur.

Conditions to avoid: Sparks, open flames, hot surfaces and strong oxidizing agents.

Incompatible materials: Strong oxidizing agents, strong acids.

Hazardous decomposition products: Carbon Monoxide, Carbon Dioxide

SECTION 11 – TOXICOLOGICAL INFORMATION

<u>Hazardous Chemicals</u>	<u>Toxicity</u>	
	<u>LD₅₀</u>	<u>LC₅₀</u>
ETHYL ALCOHOL	N/A	N/A
METHYL ALCOHOL	N/A	N/A
ETHYL ACETATE	N/A	N/A
ACETONE	N/A	N/A
POLYVINYL BUTYRAL	N/A	N/A

Likely Routes of Exposure: Inhalation, Skin Contact, Eye Contact and Ingestion.

Symptoms and Effect - Inhalation: It is a respiratory tract irritant and anesthetic and causes central nervous system depression (e.g. headache, drowsiness, dizziness, loss of coordination & fatigue). **Skin Contact:** May cause mild skin irritation. Prolonged or repeated contact may cause redness, burning, and drying and cracking of the skin. **Eye Contact:** May cause mild eye irritation. Direct contact with the liquid or exposure to vapors or mists may cause stinging, tearing and redness. **Ingestion:** Ingestion of excessive quantities may cause irritation of the digestive tract and signs of nervous system depression.

Long-Term Effect: None known.

Pre-Existing Conditions: Any pre-existing heart or skin condition or an impaired lung function.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: None known.

Persistence & Degradability: None known.

Bioaccumulative Potential: None known.

Mobility in soil: In normal use, emission of Volatile Organic Compounds (VOC's) to the air takes place, typically at a rate of ≤ 250 g/l.

SECTION 13 – DISPOSAL CONSIDERATION

Dispose of product or container in accordance with federal, state or local regulations.

SECTION 14 – TRANSPORTATION INFORMATION

Shipping Information

Shipping Name: Adhesives, Containing a Flammable Liquid
Hazardous Class: 3
I.D. Number: UN1133
Packing Group: II
Label Required: Flammable Liquid
Marine Pollutant: No

Exception to the rule: If the package that contains the hazardous material is in a small consumer size (Less than 1L), then the rules that apply to shipping hazardous materials do not apply. This is called an "Exception".
This is classified as Consumer Commodity ORM-D.

SECTION 15 – REGULATORY INFORMATION

Precautionary Label Information: Flammable, and Health Hazard.

Risk Phrases: R10-Flammable. R36/37-Irritant to eyes and respiratory system.

Safety Phrases: S2-Keep out of reach of children. S9-Keep container in a well-ventilated place. S16-Keep away from sources of ignition-No smoking. S25-Avoid contact with eyes. S26-In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S33-Take precautionary measures against static discharges.

SECTION 16 – OTHER INFORMATION

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Mfg. Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents and contractors of the information on the sheets.

DATE: 01/01/2017