



JL355 Series

4



JL240 Series

4



JL71741

4



JL23023

4

V-20® Multi Purpose PTFE Thread Sealant

A soft setting, non-petroleum based thread sealant for use where immediate pressurization is desired. Non-staining, low odor, off white in color. Use on all types of metals, reinforced fiberglass and PVC. **MIL-TT-S-1732. USDA H-2 Authorized.**
IAPMO Approved.



ISO 9001

Part Number	Net Contents & Container Type	Shipping Weight/Case	Case Equivalents	Case Qty	List Price
JL35502	1/2 pint brush top can	11 lbs.	1	12	\$ 78.45
JL35504	1 pint brush top can	19 lbs.	1	12	\$ 100.76

TFW™ Anti-Sieze Thread Sealant with PTFE

Low friction and non-toxic, TFW is used to prevent thread leaks of almost all fluids, gases or steam, even at temperatures up to 500 F. Can be used on metal, PVC, ABS and CPVC fittings and piping. **IAPMO approved.**

Part Number	Net Contents & Container Type	Shipping Weight/Case	Case Equivalents	Case Qty	List Price
JL24002	1/2 pint brush top can	9 lbs.	1	12	\$ 62.19
JL24004	1 pint brush top can	17 lbs.	1	12	\$ 86.65

Pitless Adapter Lube™ Assembly Lubricant

Preservative designed to aid in installation of pitless adapters. **USDA H-1 authorized.** Corrosion preventative contains anti-bacterial/anti-fungal additive.

Part Number	Net Contents & Container Type	Shipping Weight/Case	Case Equivalents	Case Qty	List Price
JL71741	12 oz. aerosol	13 lbs.	1	12	\$ 55.20

TF-15® Thread Sealant with PTFE for fiberglass pipe

High pressure thread sealant containing PTFE and EP additives that allow for easy breakout without seizing, stripping or galling. Highly recommended for use as a sealant on fiberglass tubing and casing threads. **Passes California COR Title 22**

Part Number	Net Contents & Container Type	Shipping Weight/Case	Case Equivalents	Case Qty	List Price
JL23023	1 gal pail	11 lbs.	1	1	\$ 377.21