




PVC Spring Check Valve Features:

- To stop backflow and syphoning.
- All water applications.
- Maintenance free operation.
- Tapered valve body design & enlarged valve chamber reduces chatter & turbulence.
- Raised radius valve seat, EPDM Seal for positive seal.
- Stainless steel spring load of 1/2 lb. or 2 lb.
- Solvent weld or male and female thread connections.
- 200 P.S.I. static pressure rating @ 72° F.
- Excess solvent cement trap - Designed to help prevent excess cement or softened material from entering into the body and sealing area during installation.
- NSF/ANSI 61+372.



1001, 1011, 1012
Series

NSF/ANSI
61+372



1011C Series

NSF/ANSI
61+372



1800 Series (hex and round)

Part Number	IPS Size	Body Length	Ctn Qty	List Price
-------------	----------	-------------	---------	------------

PVC Spring Check Valves (fip x fip)

Spring Tension 1/2 lb

1001-05	1/2"	4-1/8"	20	\$ 34.01
1001-07	3/4"	4-1/8"	20	35.30
1001-10	1"	5-1/4"	20	50.55
1001-12	1-1/4"	6-3/16"	15	68.21
1001-15	1-1/2"	6-3/16"	15	72.71
1001-20	2"	7"	10	104.68

PVC Spring Check Valves (slip x slip)

Spring Tension 1/2 lb

1011-05	1/2"	4-1/8"	20	34.11
1011-07	3/4"	4-1/8"	20	37.40
1011-10	1"	5-1/4"	20	51.62
1011-12	1-1/4"	6-3/16"	15	68.21
1011-15	1-1/2"	6-3/16"	15	72.71
1011-20	2"	7"	10	104.60
1011-25	2 1/2"		8	160.64
1011-30	3"		8	188.34

Clear

1011C-15	1-1/2"	6-3/16"	10	84.64
1011C-20	2"	7"	10	122.09

PVC Spring Check Valve, (slip x slip)

Spring Tension 2 lbs.

1012-10	1"		20	52.46
1012-12	1-1/4"		15	70.44
1012-15	1-1/2"		15	75.07
1012-20	2"		10	108.04

Foot Valve Screen (polyethylene, 100 mesh)

1800-07	3/4" hex style	2-2/5"	1	5.88
1800-10	1" round style	2-4/5"	1	7.25
1800-12	1-1/4" hex style	3"	1	10.55
1800-15	1-1/2" round style	3-2/5"	1	12.53
1800-20	2" round style	3-4/5"	1	13.71