



Elate™

Sliding bath door, 56-3/4" H x 56-1/4 - 59-5/8" W  
K-707609-6G79

## Features

- Frameless design emphasizes glass and creates a sleek, minimalist look.
- Vertical handle with inside knob on moving panel.
- Gently-curved towel bar provides integrated storage on fixed panel.
- Tempered glass ensures maximum safety and durability.
- CleanCoat® technology creates a protective barrier that repels water, prevents dirt and minerals from collecting, and makes it easier to remove hard water spots.
- Smooth, easy-to-clean wall jambs.
- Full-length moving panel seal provides excellent water containment.
- Upgrade to heavy 5/16" (8 mm) thick glass bath door by selecting K-707618-8G79.
- Coordinates with other items in the Elate collection.

## Material

- Frameless, 1/4" (6 mm) thick Crystal Clear tempered glass with rectangular grille pattern.
- Anodized aluminum prevents rust and corrosion.

## Installation

- Fits opening widths 56-1/4" - 59-5/8" (1429 - 1514 mm).
- 3-3/8" (86 mm) width adjustment.
- Out-of-plumb adjustability simplifies installation.
- Door can be installed to open to the left or right to suit your bathroom layout.
- For residential use only.
- Not for use in hospitality.

## Recommended Products/Accessories

K-23723 Faucet cleaner



## Codes/Standards

ANSI Z97.1  
CPSC 16CFR 1201

## KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

## Available Colors/Finishes

*Color tiles intended for reference only.*

### Color   Code   Description

<span style="background-color: black; width: 10px; height: 10px; display: block;"></span>	BL	Matte Black
---	----	-------------


## Available Glass Options

### Code   Description

G79	Crystal Clear with Rectangular Grille Pattern
-----	--



**Elate™**  
Sliding bath door, 56-3/4" H x 56-1/4" - 59-5/8" W  
**K-707609-6G79**



### Technical Information

All product dimensions are nominal.

Installation type: For bath installation

Opening Width - Min: 56-1/4" (1429 mm)

Opening Width - Max: 59-5/8" (1514 mm)

Walk-through - Min: 23-3/8" (594 mm)

Walk-through - Max: 26-3/4" (679 mm)

Base-To-Wall Radius – Max: 1/2" (13 mm)

Glass thickness: 1/4" (6 mm)

Glass coating: CleanCoat®

### Notes

Install this product according to the installation instructions.

The vertical opening should be a minimum of 60-1/8" (1527 mm) to allow for installation clearance.