

NH5S
Charging Hose Set
w/o Ball Valve



NH5SC
Charging Hose Set
with Ball Valve



NH5R
NH5B
NH5Y
NH5L
Individual Charging Hose
w/o Ball Valve



NH5CR
NH5CB
NH5CY
Individual Charging Hose
with Ball Valve



1/4" Color Hoses, 5 Ft Long

Main Features for All Models


- Suitable for R-410A, R-134a, R-22 and other refrigerants
- 1/4" SAE fittings with 45° bend on one end
- Leak-proof eight-sided crimp
- 800 psi working pressure, 4000 psi burst pressure
- Universal, replaceable gasket
- Adjustable depressor

Ball Valve Models

- Ball valve for reduced refrigerant loss
- Metal valve handle

NH5L

- Reverse threaded for A2L



The valve core depressor can be adjusted up or down to optimize its access to valve core. Use a valve core depressor adjustor to turn the depressor. To lower, turn clockwise; to raise, turn counterclockwise.



Model	NH5S	NH5R	NH5B	NH5Y	NH5L	NH5SC	NH5CR	NH5CB	NH5CY
Color	Red, Yellow, Blue	Red	Blue	Yellow	Orange	Red, Yellow, Blue	Red	Blue	Yellow
Quantity	pc	3	1	1	1	3	1	1	1
Ball Valve				Without ball valve				With ball valve	
Pressure Scale	psi				0-800 psi				
Length	ft				5				
Connector	in				1/4" - 1/4"				

1-YEAR WARRANTY