



QuickFacts

NPF Series



Condensing Hydro-furnace


Heating Capacity and Efficiency

Items		NPF700-060H3BH	NPF700-080H3BH	NPF700-100H5CH
Heating (gas input) natural/propane gas (BTU/h)	Max heat	60,000	80,000	100,000
	Min heat	9,000	11,000	14,000
AFUE (%)		97	97	97
AHRI number		213918723	216051340	213918724
Certified temperature rise range °F (°C)	Max heat	45-75 (25-42)		
	Min heat	5-35 (3-19)	10-40 (6-22)	10-40 (6-22)
Burner control		Modulating		

Airflow Capacity and Blower Data

Items		NPF700-060H3BH	NPF700-080H3BH	NPF700-100H5CH
Certified external static pressure	Heating	Certified external static pressure 0.1" to 1.0" WC		
	Cooling			
Airflow delivery range [CFM] (Rated ESP)	Max heat	720-1,200	950-1,400	1,200-2,000
	Min heat	350-1,200	450-1,400	400-2,000
	Cooling	1,200	1,200	2,000
Nominal cooling capacity (TON)	@400CFM	1.5-3.0	1.5-3.0	2.0-5.0
	@350CFM	1.5-3.5	1.5-3.5	2.0-5.5
Circulator blower	DxW	12" x 10"	12" x 10"	12" x 12"
	Horsepower	1/2	1/2	1
	Motor full load amps	7.6	7.6	11.0
	Motor speed & type	Variable, Electronically Commutated Motor (ECM)		

Components



Specifications

Items		NPF700-060H3BH	NPF700-080H3BH	NPF700-100H5CH
Installation type		Horizontal left		
Venting type		Forced draft direct vent or non-direct vent		
Maximum vent length	2"	70 ft.		
	3"	140 ft.		
Ignition		Electronic ignition		
Natural gas supply pressure (from source)		3.5" to 10.5" WC		
Propane gas supply pressure (from source)		8.0" to 13.0" WC		
Natural gas manifold pressure		-0.01" to -0.02" WC		
Propane gas manifold pressure		-0.01" to -0.02" WC		
Gas connection size		1/2" NPT		
Water connection size		1/4" NPT		
Condensate size		3/4" NPT		
Materials	Casing	Corrosion resistant baked on pre-painted steel		
	Combustion heat exchanger	Stainless steel		
	Hydronic heat exchanger	Copper & aluminum		
Venting	Exhaust	2" or 3" PVC, CPVC, approved PP 2" or 3" special gas vent type BH (Class III, A/B/C) 2" or 3" SS, ABS		
	Intake	2" or 3" PVC, CPVC, PP 2" or 3" special gas vent type BH (Class III, A/B/C) 2" or 3" SS, ABS		
	Vent clearance	0" to combustibles		
Safety devices		Flame rod, ignition operation detector, water temperature high limit switch, high limit sensor for exhaust temperature, Vent Installation Detector (VID), water level sensor, burner high limit sensor, Pressure Relief Valve (PRV), leak sensor		
Dimensions in (mm), WxDxH		34.5 x 31 x 17.5 (876 x 787 x 445)	34.5 x 31 x 17.5 (876 x 787 x 445)	34.5 x 31 x 21 (876 x 787 x 533)
Shipping weight lb (Kg)		145.0 (65.8)	145.0 (65.8)	167.6 (76.0)
Power supply		120V AC, 60 Hz		
Max current (A)		10.9	10.9	14.3
Circuit breaker amps (A)		15	15	20
Wire size (AWG)		14	14	12

Warranty

	Registered Furnaces	Non-Registered Furnaces
Heat exchanger	Lifetime*	20 Years**
Parts	10 Years*	5 Years**
Labor	1 Year*	1 Year**






*Limited warranties to original owner in residential applications with prompt registration.

**20-years heat exchanger, 5-year parts, and 1-year labor for non-registered furnaces.






See warranty card for complete details and restrictions.

Dimensions

NPF700-060H3BH NPF700-080H3BH



NPF700-100H5CH



Connection Size	
A Air Intake	Ø 2"
B Exhaust Gas Vent.....	Ø 2"
C Gas Connection	Ø 1.8" (NPT 1/2")
D Condensate Drain	Ø NPT 3/4"
E Overflow Connection.....	Ø 1.8" (Ø44.5 mm)
F Low Voltage Electrical Connection...	Ø 0.9" (Ø22.2 mm)
G Line Voltage Electrical Connection...	Ø 0.9" (Ø22.2 mm)
H Water Supply Connection	Ø NPT 1/4"
I Pressure Relief Valve Connection	Ø NPT 3/4" (female)



We are @Navieninc everywhere



Navien Inc. Navieninc.com 800-519-8794
20 Goodyear, Irvine, CA 92618

Navien Canada, Inc. Navieninc.ca 800-519-8794
555 Hanlan Rd., Unit 7, Vaughan, ON L4L 4R8

