

FOAM-CORE™

High strength, max foam condenser coil cleaner

Description

Foam-Core's penetrating surfactant foaming action lifts and pushes contaminants and grease out of areas of the coil which are normally inaccessible, to where they can be rinsed away with low pressure water. Leaves aluminum surfaces clean in less than five minutes. Foam-Core's powerful foaming cleaning formula is suitable for condenser coils and can be used on electronic air filters.

READ ALL SDS, DIRECTIONS AND WARNINGS ON LABEL BEFORE USE

Directions for Use:

1. Dilute FOAM-CORE with cold water only (below 100°F)

For brightening, oxides, heavy dirt & grease removal - 1 part FOAM-CORE to 3 parts water.
For some brightening, light to medium dirt & grease removal - 1 part FOAM-CORE to 6 parts water.
For no brightening, light dirt removal - 1 part FOAM-CORE to 9 parts water.
2. Shut off system.
3. Spray the diluted FOAM-CORE on to all surfaces, saturating the coils well. Use a low-pressure sprayer that does not contain aluminum. Do not use high pressure washers. Avoid back spray from wind.
4. Allow 5 minutes for full cleaning action, but never more than 8 minutes.
5. Rinse coils and surrounding area very thoroughly with low pressure water.
6. For cooking grease applications, allow the full 8 minutes before rinsing.
 Repeat if necessary.

**Characteristics | Features**

- Commercial strength
- Non-acid
- Biodegradable
- Maximum foaming action penetrates stubborn grease, tars and dirt, solubilizes and disperses them so they can be rinsed away with water
- Concentrated – dilute with water for economical use
- Leaves aluminum surfaces not only bright and shiny, but also completely clean and free of particulate matter in less than 5 minutes

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet
11050	Gallon (3.8 L)	4 Bottles	45	1.21

Specifications

Wt/Gal @ 77°F 10 lbs./gal.

Flash Point None

Color Yellow

Shelf Life 2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances



DANGER!

Causes severe skin burns and serious eye damage. May cause respiratory irritation. May be corrosive to metals.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC-DAY OR NIGHT 1-800-424-9300.

Contains: Sodium Hydroxide (CAS# 1310-73-2) and Potassium Silicate (CAS# 1312-76-1). Harmful to aquatic life. **Precautionary Statements - PREVENTION:** DO NOT mix with any acidic product. Keep reacted foam away from heat/sparks/open flames/hot surfaces. - No smoking. Keep only in original container. Wash skin thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. **RESPONSE - IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. **IF ON SKIN (or hair):** Take off all contaminated clothing immediately. Rinse skin with water/shower. Wash contaminated clothing before reuse. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. **STORAGE:** Store locked up. Store in corrosive resistant stainless steel container with a resistant inner liner. **DISPOSAL:** Dispose of contents/ container to an approved waste disposal plant. Triple rinse container (or equivalent) promptly after emptying. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Safety Data Sheet, or Call Toll Free 1-800-231-3345.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industries Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50400-0420