

Totaline® Universal Gas Valves

Totaline offers a complete line of universal gas valves including direct burner, intermittent pilot, and standing pilots. Refer to the cross reference in the back to select the correct Totaline gas valve for your next project.

Easily select the appropriate Totaline Universal Gas Valve using the chart characteristics below and/or the Gas Valve part number nomenclature.

Nomenclature: P671- X X X X

Totaline® Gas Valve

Gas Valve Type

1 = Standing Pilot
2 = Direct Burner

Stage

3 = Single
4 = Two Stage

Gas Valve Type

5 = Slow
6 = Fast

Pipe Size (inch)

7 = 1/2 x 1/2
8 = 1/2 x 3/4
9 = 3/4 x 3/4

Examples:



P671-2357



P671-2367



P671-2359



P671-2368



P671-2369



P671-2469



P671-1368



P671-1369

Part Number	Valve Type	Gas Type	Stages	Opening Style	Pipe Size (inch)	Coil Voltage	Regulator Setting (inch)	Regulator Adjustment Range
P671-2357	Direct Burner (HSI/DSI)	Bottom Outlet	1	Slow	1/2" x 1/2"	24 VAC	3.5"	Nat 2.5"-5.0" L.P. 7.0"-12.0"
P671-2367	Direct Burner (HSI/DSI)	Nat/LP	1	Fast	1/2" x 1/2"	24 VAC	3.5"	Nat 2.5"-5.0" L.P. 7.0"-12.0"
P671-2359	Direct Burner (HSI/DSI) / Proven / Intermittent Pilot	Nat/LP	1	Slow	3/4" x 3/4"	24 VAC	3.5"	Nat 2.5"-5.0" L.P. 5.0"-12.0"
P671-2368	Direct Burner (HSI/DSI) / Proven / Intermittent Pilot	Nat/LP	1	Fast	1/2" x 3/4"	24 VAC	3.5"	Nat 2.5"-5.0" L.P. 5.0"-12.0"
P671-2369	Direct Burner (HSI/DSI) / Proven / Intermittent Pilot	Nat/LP	1	Fast	3/4" x 3/4"	24 VAC	3.5"	Nat 2.5"-5.0" L.P. 5.0"-12.0"
P671-2469	Direct Burner (HSI/DSI) / Proven / Intermittent Pilot	Nat/LP	2	Fast	3/4" x 3/4"	24 VAC	Low 1.1" High 3.5"	Single Stage Nat 2.5"-5.0" L.P. 5.0"-12.0" Two Stage Nat 1.0"-3.5" Low 2.5"-5.0" High L.P. 4.0"-9.5" Low 8.0"-12.0" High
P671-1368	Standing Pilot	Nat/LP	1	Fast	1/2" x 3/4"	24 VAC	3.5"	Nat 2.5"-5.0" L.P. 7.5"-12.0"
P671-1369	Standing Pilot	Nat/LP	1	Fast	3/4" x 3/4"	24 VAC	3.5"	Nat 2.5"-5.0" L.P. 7.5"-12.0"

TOTALINE

Universal HVAC/R
Parts and Supplies