

Air Handler Heat Pump Ductless System

Indoor Model: D5FSAAH18XBK

Job Data:

Tag #:

Date:

Location:

Carrier#:



INDOOR STANDARD FEATURES


- Modes: Cool, Heat, Dry, Fan, Auto
- 4-way installation (Up flow, Down flow, Right, Left)
- Auto-Restart function
- Quiet indoor operation
- Aluminum hydrophilic pre-coated fins

RESIDENTIAL APPLICATION LIMITED WARRANTY*

- Ten (10) years if properly registered within ninety (90) days after original installation, parts are warranted to the original purchaser for a period of ten (10) years. Otherwise, parts warranty is five (5) years.

NOTE: Images for illustration purposes only. Actual models may be slightly different.

D5FSAAH18XBK			
System	Indoor Model #		D5FSAAH18XBK
	Indoor Size		18000
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208-230/1/60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	3
Operating Range	Cooling Indoor DB Min - Max	°F(°C)	60~90 (16~32)
	Heating Indoor DB Min - Max	°F(°C)	32~86 (0~30)
Indoor Coil	Face Area	Sq. Ft.	3
	No. Rows		3
	Fins per inch		20
	Circuits		6
Indoor Unit	Number of Fan Speeds		550/510/450
	Airflow (highest to lowest)	CFM	618.0 / 576.8 / 529.7 / 488.5 / N\A
	Sound Pressure (highest to lowest)	dB(A)	N\A/42.5/37.5/30.0/N\A
Dimensions	Height	in (mm)	45.00(1143)
	Width	in (mm)	17.52(445)
	Depth	in (mm)	21.02(534)
	Net Weight	lbs (kg)	104.72(47.5)
	Shipping Height	in (mm)	21.20(640)
	Shipping Width	in (mm)	48.23(1225)
	Shipping Depth	in (mm)	21.06(535)
	Shipping Net Weight	lbs (kg)	125.66(57)
CONTROLS			
Standard	Wireless Remote Controller (°F/°C Convertible)		
Optional	Wired Remote Control 7 Day Programmable	KSACN1401AAA	
	24V Mini Interface	KSAIC0601230	



INDOOR UNIT DIMENSIONS					
Dimensions		18K/24K		36K	
		Inch	mm	Inch	mm
A	Model Height	45	1143	49	1245
B	Model Width	17.5	445	21	534
C	S.A. Opening Width	15.6	397	19.1	486
D	R.A. Opening Width	15.1	384	18.6	473
E	Model Depth	21	534	21	534
F	S.A. Opening Depth	10.3	260	10.3	260
G	R.A. Opening Depth	18.8	476	18.8	476
H	S.A. Opening Clearance	0.9	24	0.9	24
I	R.A. Opening Side Clearance	1.3	32	1.3	32
J	R.A. Opening Front Clearance	1.5	38	1.6	41
K	R.A. Opening Back Clearance	0.6	16	0.6	16



R-454B