

G	<div style="display: flex; align-items: center;"> <div style="flex: 1;"> <p>JAY R. SMITH MFG. CO.® DIVISION OF SMITH INDUSTRIES, INC. POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com</p> </div> <div style="flex: 1; text-align: center;"> <p>MEMBER OF:</p> </div> </div>				LOCATION	
	<h2 style="margin: 0;">URINAL SUPPORTS</h2> <h3 style="margin: 0;">FOR OFF-THE-FLOOR URINALS</h3> <h4 style="margin: 10px 0 0 0;">WITH SUPPORTING STUDS AND ADJUSTABLE COUPLING FOR BLOWOUT URINALS</h4>					
DRAWING NUMBER	S0632					
SIZE	A					
SCALE:	NONE					
DATE:	11-13-69					
APPROVED BY:	RP					
CHECKED BY:	RVB					
DRAWN BY:	RVB					
FIGURE NUMBER	0632, 0633					

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA

Fig. 0632
3 1/4 (83) MIN
5 3/4 (135) MAX

Side View

Fig. 0633
4 3/4 (120) MIN
7 1/2 (190) MAX

Front View

Fig. 0632 . . . 2" (50) Outlet Connection

Fig. 0633 . . . 3" (80) Outlet Connection

NOTE: Coupling should extend 5/8" (16) beyond finished wall.

FIXTURE MFG.	NAME	NUMBER	A	B	D	E
Am. Std.	Jet Brook	6570-Ser.	19 1/2 (495)	17 1/2 (445)	7 (180)	6 (150)
Crane	Expedio	7-101, 3	22 (560)	19 1/2 (495)	7 (180)	5 (125)
Crane	Expedio	7-104	22 (560)	19 1/2 (495)	7 (180)	7 (180)

Face Plate

Collar

The water closet gasket regularly furnished is made of molded neoprene and designed to fit water closet outlet dimensions and configurations shown in ANSI Standard A112.19.2M-1982, Figure 13B. If gasket is not found to be compatible to fixture due to nonconformance of said fixture to ANSI A112.19.2M, then fixture manufacturer shall be consulted for a suitable gasket recommendation. Jay R. Smith assumes no liability for connections to fixtures which do not conform to these standards.

NOTE: All support bases must be securely anchored to a rigid floor and/or other rigid substructure with (4) 1/2" bolts furnished by others.

NOTE: Dimensions shown in parentheses are in millimeters.