

Features

- Small/large bowl.
- No faucet holes; requires wall- or counter-mount faucet.
- Luster finish.
- Includes reveal and no-reveal option.
- SilentShield® sound-absorption technology offers quieter performance.
- 11409-L = single pack.
- J11409-L = 3 per pack.
- T11409-L = 20 per pack.
- F11409-L = 40 per pack.
- Right-hand versions also available.
- 31-3/4" (806 mm) x 20-3/4" (527 mm) x 8" (203 mm)

Material

- 18-gauge stainless steel.

Installation

- Under-mount.

Recommended Accessories

7400 Duostrainer™ Sink Strainer
11862 Bottom Bowl Rack
11863 Bottom Bowl Rack
K-6139 Sponge Caddy

Components

Product includes:

91915 Hardware Kit



Codes/Standards

ASME A112.19.3/CSA B45.4

STERLING® Warranty - Stainless Steel Sinks

See website for detailed warranty information.



Under-mount Kitchen Sink

A technical drawing showing a cross-section of a mechanical assembly. A component, possibly a valve or a plug, is being inserted into a slot within a larger block. The component has a central vertical shaft and a flange. The block has a hatched pattern on its upper right portion. A cable or hose is connected to the side of the block.

Technical drawing of the 24-inch wide, 18-inch high, two-basin stainless steel sink. The drawing includes top and side views with dimensions in inches and millimeters.

Top View Dimensions:

- Total Width: 31-3/4" (806 mm)
- Total Height: 20-3/4" (527 mm)
- Basin Width: 15-7/8" (403 mm)
- Basin Height: 10-3/8" (264 mm)
- Mounting Hole Spacing: 8-1/4" (210 mm)
- Mounting Hole Offset from Front Edge: 9" (229 mm)
- Mounting Hole Diameter: 1-1/8" (29 mm)

Side View Dimensions:

- Total Height: 18" (457 mm)
- Mounting Hole Offset from Front Edge: 9" (229 mm)

The drawing also shows the SilentShield™ Sound Pads at the base of the basins.

Use the supplied cut-out template to select either a hidden or exposed rim.